



# “Delano” Gas Direct Vent (IPI Ignition) (#DEL-36)

The **Delano** model (Electronic Ignition) comes standard with a decorative black curved firebox lining, remote modulating valve system w/ flame & fan adjustment. (remote control & light kit included)

## STANDARD FEATURES

- 26,000 BTU/hr Input - NG & 25,500 BTU/hr Input - LP
- High Efficiency: Natural Gas - 79.8% LP Gas - 81.18%
- Canada P-4 Approved
- High Quality, Quick-Latch, Lifetime Glass (23¾" X 30 1/16")
- Black Firebox Lining (curved design)
- Light Kit (bottom)
- Remote Control - Thermostatic (Flame, Light & Fan adjustment)
- High-Low Regulator
- Engineer-Designed burner system
- Minnesota Energy Code Compliant to 50 pascals

## \*\*REQUIRED FOR INSTALLATION\*\*

- Glass Media Kit (various colors available)
- Contemporary Frame/Face (various designs & finishes available)

## OPTIONAL FEATURES

- Automatic Fan kit (1) -75 CFM
- Stainless Firebox Liner Overlay (curved design)
- Rock Media (must be used with required glass media)
- Flame Accent Media (must be used with required glass media)

## SAFETY

- EACH FIREPLACE FACTORY TESTED!
- Tested by OMNI-Test Laboratories  
Complies with ANSI-Z21.88-2009•CSA 2.33-2009  
'Vented Gas Fireplace Heaters'
- U.S. & Canadian Installation Approved
- Sealed Combustion Chamber
- Removable Control Board with 30-Second Safety Pilot
- Automatic Pressure Relief Glass System
- Battery Back-Up
- Bedroom & Mobile Home Approved

## SPECIFICATIONS

- Height: 32"                      ■ Weight: 150 lbs.
- Width: 35⅝"
- Depth: 15¼"                    ■ Back Width: 27 7/8"

## FRAMING DIMENSIONS

- Height: 37½"                    ■ Width: 36⅜"                    ■ Depth: 15¾"

**NOTE:** Refer to the Delano's installation manual for complete installation & venting requirements.

## CLEARANCES

- From fireplace face top to framing.....5 ½"
- From fireplace left & right sides & back.....¼"
- Fireplace bottom to flooring.....0"
- Fireplace top to ceiling.....31"
- Fireplace side to adjacent sidewall.....1 ½"
- Mantel 4" deep from top of fireplace\*.....16"

\*Refer to Mantel Requirement in the fireplace installation manual.

## VENTING SYSTEMS & REQUIREMENTS

**This fireplace is manufactured to accept 5"x 8" pipe only.**

- Simpson Dura-Vent™ DV-PRO Pipe - 5"x 8"
- Selkirk Metalbestos™ Direct Chimney System - 5"x 8"
- Ameri-Vent™ Direct Chimney System - 5"x 8"
- Metal Fab™ 5"x 8"
- Security™ 5"x 8"
- ICC™ 5"x 8"
- Kozy Heat Flexible #800 series Vent Kits\* - 5"x 8"

**IMPORTANT:** Kozy Heat Part #800-WPT or #800-WPT2, must be used on ALL Horizontal vent runs.

The included Horizontal Vent Heat Shield must be installed when using a 90° elbow to horizontally position the vent system. This includes corner installation.

**Elbows:** For each additional 90° elbow used after the first elbow, 3 ft. must be subtracted from the maximum venting allowed. For each additional 45° elbow used after the first elbow, 1½ ft. must be subtracted from the maximum venting allowed.

Note: (2) 45° elbows = (1) 90° elbow.

### Horizontal Terminations

Minimum: 6"                      Maximum: 25 ft.\*

\*30 ft. maximum allowed when using stainless steel pipe

### Vertical Terminations

Minimum: 4 ft.                    Maximum: 40 ft.

### HORIZONTAL / VERTICAL COMBO:

40 Ft = 20 FT. maximum horizontal / 20 ft. maximum vertical  
(consult the horizontal & vertical combination venting chart in the installation manual)

Features, Options & Specifications are subject to change.